

SPECIFICATION

T125, T155 Series



T125 Suggested Specification:

Heavy duty, steel single deflection supply grille shall be Tuttle & Bailey model T125. The grille shall be available with horizontal (H) or vertical (V) blades. The grille shall have individually adjustable blades on 1/2" centers. Construction shall consist of 14 gauge steel blades and an 18 gauge steel margin with a 1-1/4" wide border on all sides with mitered corners. The grille shall be available with countersunk screw holes for a clean, unobtrusive appearance.

Finish shall be Tuttle & Bailey White (WH) electrocoat finish. The finish shall be an anodic acrylic paint, baked at 315°F for 30 minutes with a pencil hardness of HB to H.

T155 Suggested Specification:

Heavy duty, steel double deflection supply grille shall be Tuttle & Bailey model T155. The grille shall be available with horizontal (H) or vertical (V) front blades. The grille shall have individually adjustable front blades on 1/2" centers and individually adjustable rear blades on 3/4" centers.

Construction shall consist of 14 gauge steel front blades and an 18 gauge steel margin with a 1-1/4" wide border on all sides with mitered corners. The grille shall be available with countersunk screw holes for a clean, unobtrusive appearance.

Optional volume adjustment damper (Model SOBD) shall be operable from face and constructed of heavy gauge steel.

The paint finish shall be the Tuttle & Bailey White (WH) or Mill (ML).

The manufacturer shall provide published performance data tested in accordance with ANSI/ASHRAE Standard 70-1991 at isothermal conditions.

Finish shall be Tuttle & Bailey White (WH) electrocoat finish. The finish shall be an anodic acrylic paint, baked at 315°F for 30 minutes with a pencil hardness of HB to H.

