

## **SPECIFICATIONS**

T125, T155

## **T125 Suggested Specification:**

Heavy duty, steel single deflection supply grille shall be Tuttle & Bailey model T125. The grille shall be available with horizontal (H) or vertical (V) blades. The grille shall have individually adjustable blades on 1/2" centers. Construction shall consist of 14 gauge steel blades and an 18 gauge steel margin with a 1-1/4" wide border on all sides with mitered corners. The grille shall be available with countersunk screw holes for a clean, unobtrusive appearance.

Optional volume adjustment damper (Model SOBD) shall be operable from face and constructed of heavy gauge steel.

The manufacturer shall provide published performance data tested in accordance with ANSI/ASHRAE Standard 70-1991 at isothermal conditions.

Finish shall be Tuttle & Bailey White (WH) electrocoat finish. The finish shall be an anodic acrylic paint, baked at 315°F for 30 minutes with a pencil hardness of HB to H.

## T155 Suggested Specification:

Heavy duty, steel double deflection supply grille shall be Tuttle & Bailey model T155. The grille shall be available with horizontal (H) or vertical (V) front blades. The grille shall have individually adjustable front blades on 1/2" centers and individually adjustable rear blades on 3/4" centers. Construction shall consist of 14 gauge steel front blades and an 18 gauge steel margin with a 1-1/4" wide border on all sides with mitered corners. The grille shall be available with countersunk screw holes for a clean, unobtrusive appearance.

Optional volume adjustment damper (Model SOBD) shall be operable from face and constructed of heavy gauge steel.

The manufacturer shall provide published performance data tested in accordance with ANSI/ASHRAE Standard 70-1991 at isothermal conditions.

Finish shall be Tuttle & Bailey White (WH) electrocoat finish. The finish shall be an anodic acrylic paint, baked at 315°F for 30 minutes with a pencil hardness of HB to H.

