



Submittal Drawing

- Heavy extruded aluminum blades in a 20 gauge steel margin
- Individually adjustable, aerodynamically shaped blades on 3/4" spaced centers
- · Available with both horizontal blades and vertical blades
- Available in sizes ranging from 6" x 4" to 48" x 48" in 1" increments; larger sizes will ship in multiple sections
 with assembly hardware for field assembly
- Standard finish is white (WH)





Mounting Style

A - External Screw Holes

C - Concealed Screw Holes with Brackets

N - No Screw Holes

Finish

WH - White

AP - Aluminum Paint

OW - Off-White

FB - Flat Black

MP - Match Paint

Accessories

SOBDS - Steel Opposed Blade Damper,

Slot Operated

AOBDS - Aluminum Opposed Blade

Damper, Slot Operated

ST - Earthquake Tabs

SM - Insect Screen, 1/16" Square Mesh

LM - Debris Screen, 1/4" Square Mesh

45 - Steel Plaster Frame

A45 - Aluminum Plaster Frame

Dimensions in inches

Job: Location:	Tag:		AVS50 / ASV60
	Submitted By:		AeroFoil Grille/Register Steel Margin Single Deflection
Contractor:	SD - 2280	Rev: A (04/18)	3/4" Blade Spacing